

Dimensión, espesor pared, peso tubo acero inoxidable ASME B36.10M y B36.19

Diámetro In	O.D.	Espesor de pared y peso									
	ASTM	Sch. 5S		Sch. 10S		Sch. 40S		Sch. 80S		Sch. 160S	
	mm	mm	Kg/m	mm	Kg/m	mm	Kg/m	mm	Kg/m	mm	Kg/m
1/8	10.3			1.25	0.28	1.73	0.37	2.42	0.47		
1/4	13.7			1.66	0.49	2.24	0.63	3.03	0.80		
3/8	17.2			1.66	0.63	2.32	0.85	3.20	1.10		
1/2	21.3	1.66	0.81	2.11	1.00	2.77	1.27	3.74	1.62	4.78	1.90
3/4	26.7	1.66	1.02	2.11	1.28	2.87	1.68	3.92	2.20	5.57	2.90
1	33.4	1.66	1.30	2.77	2.09	3.38	2.50	4.55	3.24	6.35	4.20
1-1/4	42.2	1.66	1.66	2.77	2.69	3.56	3.39	4.86	4.47	6.35	5.60
1-1/2	48.3	1.66	1.91	2.77	3.11	3.69	4.06	5.08	5.41	7.14	7.20
2	60.3	2.11	2.40	2.77	3.93	3.92	5.45	5.54	7.49	8.74	11.1
2-1/2	73.0	2.11	3.69	3.05	5.26	5.16	8.64	7.01	11.4	9.53	14.9
3	88.9	2.11	4.52	3.05	6.46	5.49	11.3	7.62	15.3	11.13	21.3
3-1/2	101.6	2.11	5.18	3.05	7.41	5.74	13.6	8.08	18.6	---	---
4	114.3	2.11	5.84	3.05	8.37	6.02	16.1	8.56	22.3	13.49	33.5
5	141.3	2.77	9.46	3.41	11.6	6.56	21.8	9.53	31.0	15.88	49.1
6	168.3	2.77	11.3	3.41	13.9	7.12	28.3	10.98	42.6	18.27	67.6
8	219.1	2.77	14.8	3.76	20.0	8.18	42.5	12.70	64.6	23.02	111
10	273.1	3.41	22.7	4.20	27.8	9.28	60.4	12.70	81.5	28.58	172
12	323.9	3.97	31.3	4.58	36.1	9.53	73.9	12.70	97.4	33.33	239